

## PRODUCT DATA SHEET

# Sikalastic® Rapid Filler Paste

A rapid-setting, proprietary formulation polymethyl methacrylate (PMMA) heavy paste

### PRODUCT DESCRIPTION

Sikalastic® Rapid Filler Paste is a two-component polymethyl methacrylate-based (PMMA) heavy paste.

### USES

Used to fill small cracks, depressions and voids in non traffic bearing horizontal or vertical substrates after priming and prior to application of Sikalastic® Rapid systems. Sikalastic® Rapid Filler Paste can also be used to smooth out laps on Sikalastic® Rapid-723 and Sikalastic® Rapid-723 WG membranes when applying aesthetic top coats or surfacing on roofing and non-traffic bearing waterproofing applications.

### CHARACTERISTICS / ADVANTAGES

- Rapid curing
- Easy to apply
- Provides same-day installation

## PRODUCT INFORMATION

Chemical Base	Two-component polymethyl methacrylate (PMMA) resin
Packaging	2.85 gallon (10.6 L) pails, 33.1 lbs (15 kg) per pail, 36 per pallet
Color	Gray
Shelf Life	Sikalastic® Rapid Filler Paste has a shelf life of up to 12 months in the original unopened pail when properly stored, sealed and unmixed.
Storage Conditions	Store in a tightly closed container in a cool, dry, ventilated area away from heat and oxidizing agent. Do not store in direct sunlight or in temperatures below 55°F (13°C) or above 80°F (27°C).
Density	11.6 lb/gal (1.39 g/ml) @ 73.4°F (23°C) (ASTM D-1475)
Volatile organic compound (VOC) content	See Product Safety Data Sheet
Testing	64 Shore A Hardness (ASTM D-2240)

## APPLICATION INFORMATION

Mixing Ratio	Temperature Range	Catalyst required (per liter of resin)
	32°F to 50°F (0°C to 10°C)	8 tablespoons (80 g)
	50°F to 68°F (10°C to 20°C)	6 tablespoons (60 g)
	68°F to 95°F (20°C to 35°C)	3 tablespoons (30 g)
Product Temperature	37°F to 86°F (3°C to 30°C)	
Ambient Air Temperature	32°F to 95°F (0°C to 35°C)	
Substrate Temperature	32°F to 122°F (0°C to 50°C)	
Pot Life	15 - 20 minutes @ 68°F (20°C) All working and cure times are approximate and may vary upon wind, humidity and ambient/surface temperatures.	
Cure Time	3 hours @ 68°F (20°C) All working and cure times are approximate and may vary upon wind, humidity and ambient/surface temperatures.	
Waiting / Recoat Times	60 minutes @ 68°F (20°C) All working and cure times are approximate and may vary upon wind, humidity and ambient/surface temperatures.	

## BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

## AVAILABILITY/WARRANTY

### AVAILABILITY

From Sika Corporation – Roofing Authorized Applicators for use within American Hydrotech systems.

### WARRANTY

Upon successful completion of the installed roof by the Sika Authorized Applicator in compliance with Sika

requirements, Sika Corporation will provide a warranty to the Building Owner via the Sika Authorized Applicator.

## LIMITATIONS

- Sikalastic® Rapid Filler Paste should not be used for repairs on pedestrian or vehicular traffic bearing substrate.

## APPLICATION INSTRUCTIONS

### SUBSTRATE PREPARATION

All work surfaces should be clean, dry, free of dirt, dust, debris, oils and other contaminants.

## MIXING

Thoroughly stir the entire container of Liquid resin with a slow-speed (200 to 400 rpm) mechanical mixer (electric drill with a mixing blade) for two minutes before each use. Only catalyze the amount of material that can be used within 10 to 15 minutes. Add pre-measured Catalyst Powder to the resin component, stir for 2 minutes. The amount of catalyst required is determined by resin weight and ambient temperature

## APPLICATION

After mixing, apply Sikalastic® Rapid Filler Paste to clean and prepared substrate at the required consumption using a spatula or a trowel. The resin should be spread evenly onto the surface.

## OTHER RESTRICTIONS

See Legal Disclaimer.

## LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at [usa.sika.com](http://usa.sika.com) or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/about-us/terms-conditions-of-sale.html> or by calling 1-800-933-7452.

### Sika Corporation

201 Polito Avenue  
Lyndhurst, NJ 07071  
Phone: +1-800-933-7452  
Fax: +1-201-933-6225  
[usa.sika.com](http://usa.sika.com)



### Product Data Sheet

Sikalastic® Rapid Filler Paste  
May 2026, Version 02.01  
020915402000244936

SikalasticRapidFillerPaste-en-US-(05-2026)-2-1.pdf

