



## PRODUCT DATA SHEET

# Sikalastic® Rapid Cleaner PMMA

Solvent- Based Cleaner

### PRODUCT DESCRIPTION

Sikalastic® Rapid Cleaner PMMA is a solvent-based solution, formulated to clean and reactivate fully cured Sikalastic Rapid membranes.

### USES

Sikalastic® Rapid Cleaner PMMA is ideal for cleaning tools and for preparing metal and plastic substrates for application of Sikalastic Rapid resin or Sikalastic Rapid components.

### CHARACTERISTICS / ADVANTAGES

- Compatible with Sikalastic Rapid PMMA resins
- Compatible with Liquid Flashing resins

## PRODUCT INFORMATION

<b>Chemical Base</b>	Solvent-based liquid
<b>Packaging</b>	5 Gal (18.9 L) pail
<b>Color</b>	Clear
<b>Shelf Life</b>	Sikalastic® Rapid Cleaner PMMA has an approximate shelf life of 12 months from the time of shipment when tightly sealed, unmixed, and stored properly.
<b>Storage Conditions</b>	Store in a clean, dry, well-ventilated location and protect from freezing. Avoid prolonged rooftop storage or direct sunlight. Storage temperatures should range from 55° - 80°F (13°-27°C).
<b>Flash Point</b>	6°F (-14°C) <span style="float: right;">ASTM D93</span>
<b>Volatile organic compound (VOC) content</b>	See Product Safety Data Sheet
<b>Ambient Air Temperature</b>	40°F - 95°F (5°C - 35°C)
<b>Adjustability Time</b>	60 minutes @ 68°F (20°C) All working and cure times are approximate and may vary upon wind, humidity, and ambient/ surface temperatures.
<b>Drying Time</b>	20 minutes @ 68°F (20°C) All working and cure times are approximate and may vary upon wind, humidity, and ambient/ surface temperatures.

## BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

## AVAILABILITY/WARRANTY

### AVAILABILITY

From Sika Corporation – Authorized Applicators for use within Sika roofing systems

### WARRANTY

Upon successful completion of the installed roof by the Sika Authorized Applicator in compliance with Sika requirements, Sika Corporation will provide a warranty to the Building Owner via the Sika Authorized Applicator.

## ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current Safety Data Sheets before using any

products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887

## APPLICATION INSTRUCTIONS

### APPLICATION

Apply Sikalastic® Rapid Cleaner PMMA using a lint free cloth. Thoroughly wipe down the surface membrane and allow the area to dry for approximately 20 minutes. Once clean, follow up with application of Sikalastic Rapid products within 60-minutes.

## LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates (“SIKA”), the user must always read and follow the warnings and instructions on the product’s most current product label, Product Data Sheet and Safety Data Sheet which are available at [usa.sika.com](http://usa.sika.com) or by calling SIKA’s Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the

current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/about-us/terms-conditions-of-sale.html> or by calling 1-800-933-7452.

**Sika Corporation**

201 Polito Avenue  
Lyndhurst, NJ 07071  
Phone: +1-800-933-7452  
Fax: +1-201-933-6225  
[usa.sika.com](http://usa.sika.com)



**Product Data Sheet**  
Sikalastic® Rapid Cleaner PMMA  
May 2026, Version 02.01  
020915402000246529

SikalasticRapidCleanerPMMA-en-US-(05-2026)-2-1.pdf

