



PRODUCT DATA SHEET

Sikalastic® Rapid Color

Color additive

PRODUCT DESCRIPTION

Sikalastic® Rapid Color is a resin color pigment additive mixed with unpigmented Sikalastic® Rapid resin.

USES

Used as a color additive to unpigmented Sikalastic Rapid resin.

CHARACTERISTICS / ADVANTAGES

- Pre-measured for easy application
- Non-toxic, low odor
- Easy to mix

PRODUCT INFORMATION

Packaging	3.3 lb (1.5 kg) pouch
Color	White, Gray, Beige, Yellow, Green, Blue, Red, and Black Custom colors available with minimum order requirements. For lead time and minimum order requirements, contact Sika Roofing Customer Service
Shelf Life	Up to 12 months in the original unopened pail when properly stored, sealed and unmixed.
Storage Conditions	Store in a tightly closed container in a cool, dry, ventilated area away from heat and oxidizing agent. Do not store in direct sunlight or in temperatures below 55°F (13°C) or above 80°F (27°C).
Volatile organic compound (VOC) content	See Product Safety Data Sheet
Mixing Ratio	1 pouch per pail of Sikalastic Rapid resin

BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

AVAILABILITY/WARRANTY

AVAILABILITY

From Sika Corporation – Sika Authorized Applicators for use within Sika membrane systems.

ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

APPLICATION INSTRUCTIONS

MIXING

The Sikalastic Rapid resin should be thoroughly mixed before adding the color additive. Using a slow-speed (200-400 rpm) mechanical agitator, mix the liquid resin for 2 - 5 minutes. Next, add the entire contents of Sikalastic® Rapid Color to the liquid resin and continue mixing for 2 - 5 minutes until uniform streak-free color is achieved.

NOTE:

Combining Sikalastic® Rapid Color with Sikalastic Rapid resins does not affect pot life or cure time of the product.

OTHER RESTRICTIONS

See Legal Disclaimer.

LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates (“SIKA”), the user must always read and follow the warnings and instructions on the product’s most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA’s Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product’s shelf life. User determines suitability of product for intended use and assumes all risks. User’s and/or buyer’s sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT**

OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/about-us/terms-conditions-of-sale.html> or by calling 1-800-933-7452.

Sika Corporation

201 Polito Avenue
Lyndhurst, NJ 07071
Phone: +1-800-933-7452
Fax: +1-201-933-6225
usa.sika.com



Product Data Sheet
Sikalastic® Rapid Color
May 2026, Version 02.01
020915402000246373

SikalasticRapidColor-en-US-(05-2026)-2-1.pdf

