HYDROTECH®

GARDENHATCH®

12"-18" WIDE RECOMMENDED **VEGETATION-FREE ZONE** SYSTEMFILTER FABRIC -**INSTALL UNDER BALLAST AND GARDENHATCH** UP SIDES OF GARDENHATCH **INSPECTION** AND GARDENEDGE METAL **CHAMBER EDGING** WITH EXTENSION DRAINAGE LAYER STYROFOAM INSULATION (OPTIONAL) **ROOF DRAIN** ROOTSTOP / **ROOTSTOP HD HYDROFLEX 30** HYDROTECH MONOLITHIC MEMBRANE (MM6125) WATERPROOFING AT APPROVED SUBSTRATE DRAINS PER HYDROTECH RECOMMENDATIONS

NOTES:

- 1. MULTIPLE DRAINAGE LAYER OPTIONS ARE AVAILABLE. DRAINAGE LAYER MAY BE ADDED UNDER THE STONE BALLAST OR PAVERS FOR ADDITIONAL RETENTION. SEE INDIVIDUAL COMPONENT DETAILS (GR-1 SERIES) FOR DRAINAGE LAYER DETAILS.
- 2. THE RECOMMENDED VEGETATION FREE ZONE (VFZ) MAY BE COMPOSED OF TYPICAL STONE BALLAST OR CONCRETE PAVERS.
- 3. GARDENHATCH INSPECTION CHAMBER DIMENSIONS:
 - CHAMBER: 11" x 11" OR 18" x 18" WITH 4" FLANGE (ALL SIDES)
 - CHAMBER HEIGHT: 4.75"
 - EXTENSION HEIGHTS: 1", 3" OR 8.5" (UP TO 25.5" DEPTH)
 - CHAMBER LID: 11" x 11" or 18" x 18"