





#### NOTES:

1. SIZE WIDTH OF DE-BONDING TAPE TO PROVIDE UN-BONDED AREA MINIMUM 5X LARGER THAN MAXIMUM ANTICIPATED MOVEMENT. FOR STATIC JOINTS, TAPE SHOULD EXTEND 2" PAST EDGES OF THE PLANKS.
2. ANY MOVEMENT MAY CAUSE MINOR COSMETIC CRACKING/CRAZING IN ANY FINISH TOPCOAT AND/OR SURFACING APPLIED.
3. APPLICATION OF APPROPRIATE SIKALASTIC RAPID PRIMER MUST PRECEDE APPLICATION OF SIKALASTIC RAPID RESINS.
4. ALL SIKALASTIC RAPID FLEECE, INCLUDING OVERLAPS, MUST BE SET IN AND COVERED OVER WITH SIKALASTIC RAPID RESIN.

**BUILDING TRUST**  
312-337-4998



## PRECAST CONCRETE DECK OR WALL JOINT TREATMENT

SCALE:

N.T.S.

DATE:

05-2026

FILE NO.:

PMMA

DRW. NO.:

SR-5A

AS A MEMBRANE MANUFACTURER, SIKA CORPORATION ("SIKA") REVIEWS DETAILS PREPARED BY THE CONSULTANT, ARCHITECT AND/OR ENGINEER FOR A PROJECT SOLELY FOR THE PURPOSE OF DETERMINING IF A SIKA WARRANTY MAY ISSUE FOR THE PROJECT. THIS REVIEW IS NOT TO BE CONSTRUED AS APPROVAL OF DETAILS BY SIKA AND IS NOT BEING CONDUCTED IN LIEU OF SOUND ENGINEERING AND ARCHITECTURAL PRACTICES AND JUDGMENT AND SHOULD NOT BE RELIED UPON FOR THAT PURPOSE. SIKA CORPORATION ASSUMES NO LIABILITY WITH RESPECT TO THE DESIGN OF THE ROOFING OR WATERPROOFING SYSTEM. THE ARCHITECT, CONSULTANT AND/OR ENGINEER OR DESIGN PROFESSIONAL FOR A PARTICULAR PROJECT BEARS THE SOLE RESPONSIBILITY FOR THE DESIGN OF THE ROOFING OR WATERPROOFING SYSTEM, FOR THE PREPARATION AND APPROVAL OF THE DETAILS AND SHOP DRAWINGS, AND FOR DETERMINING THEIR SUITABILITY FOR A PARTICULAR PROJECT OR APPLICATION. WHILE SIKA PROVIDES GENERAL INSTRUCTIONS FOR THE INSTALLATION OF ITS MEMBRANE AS WELL AS TRAINING FOR SIKA AUTHORIZED APPLICATORS, THE MEANS AND METHODS USED BY THE CONTRACTOR FOR SURFACE PREPARATION AS WELL AS THE MEANS AND METHODS EMPLOYED BY THE CONTRACTOR IN THE INSTALLATION OF THE SIKA MEMBRANE ARE THE RESPONSIBILITY OF THE CONTRACTOR. ALL SALE OF SIKA PRODUCTS AND SERVICES ARE SUBJECT TO SIKA'S TERMS AND CONDITIONS OF SALE AVAILABLE AT HYDROTECHUSA.COM.